

Abstract Submission for Space Internet Workshop

June 4-5, 2003 - Cleveland, Ohio

Author: David Andrew Carek, P.E.
Affiliation: NASA Glenn Research Center, Satellite Networks and Architectures
Address: M.S. 54-5
21000 Brookpark Road
Brookpark, OH 44135
Phone: (216) 433-8396
Email: David.A.Carek@nasa.gov

Title: Shuttle Payload Ground Command and Control – An Experiment Implementation for STS-107

Abstract:

This presentation covers the design of a command and control architecture developed by the author for the Combustion Module-2 microgravity experiment, which flew aboard the STS-107 Shuttle mission. The design was implemented to satisfy a hybrid network that utilized TCP/IP for both the onboard segment and ground segment, with an intermediary unreliable transport for the space to ground segment.

With the infusion of Internet networking technologies into Space Shuttle, Space Station, and spacecraft avionics systems, comes the need for robust methodologies for ground command and control. Considerations of high bit error links, and unreliable transport over intermittent links must be considered in such systems. Internet protocols applied to these systems, coupled with the appropriate application layer protections, can provide adequate communication architectures for command and control. However, there are inherent limitations and additional complexities added by the use of Internet protocols that must be considered during the design.

This presentation will discuss the rationale for the framework and protocol algorithms developed by the author. A summary of design considerations, implantation issues, and lessons learned will be presented. A summary of mission results using this communications architecture will be presented. Additionally, areas of further needed investigation will be identified.

Shuttle Payload Ground Command and Control

**An Experiment Implementation
Combustion Module-2 Software Development, STS-107**


**Presented at the Space Internet Workshop III
Cleveland, Ohio
June 4, 2003**



Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field



Combustion Module-2

Ground Command & Control

- System Overview
- Design Considerations
- Protocol Overview
- Implantation Issues
- Lessons Learned
- Summary of Mission Results
- Areas for Further Investigation



Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field



CM-2 Software Team



Top Row: Jonancy Colbrunn, Alan Richard, Steve Lux, Kevin Carmichael, Laura Maynard-Nelson, Lisa VanderAar, Dan Taylor

Bottom Row: Len Marinis, David Carek, Jeff Spiegler


Not Pictured: Richard Woodward, Kin Wong, Laszlo Szijarto



Glenn Research Center


David Andrew Carek, P.E.

at Lewis Field




System Overview

SPACEHAB Carrier




STS-107 SPACEHAB Payload
Module Integration - Cape Canaveral



Glenn Research Center

David Andrew Carek, P.E.


at Lewis Field




System Overview

Microgravity Combustion Experiments




LSP



SOFBALL



Mist



See Ref. 1 for further information on these experiments



Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field



System Overview

Communications Interfaces SpaceLab/SPACEHAB

- SpaceLab - STS-83, STS-94
 - Main Computer I/F – RAU (Remote Acquisition Unit)
 - **Uplink Test Parameters Only**
- SPACEHAB – STS-107
 - Main Computer I/F – Ethernet
 - **Full Ground Commanding**
 - **File Downlink**



Glenn Research Center


David Andrew Carek, P.E.

at Lewis Field



System Overview


End to End Communications Path



Glenn Research Center


David Andrew Carek, P.E.

at Lewis Field



System Overview


CM-2 Payload Communications Interfaces



Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field



Communications Design Considerations

- Command Protocol Requirements
 - Flight computer must verify command integrity
 - No end-to-end TCP data integrity
 - Even if end-to-end, TCP checksum not good enough (Ref. 3,4)
 - Ground computer must verify command was processed
 - Must handle arbitrary data errors
 - Multiple bit errors
 - Partial/complete packet loss
 - Multiple consecutive packet loss
 - Long term or intermittent LOS
 - Must work for both PGSC (onboard) and ground commanding




Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field



Generic Command Verification Protocol Overview



1. Command Sender generates unique CRC signature by appending timestamp to command prior to CRC calculation
2. Command Sender transmits command to Command Receiver
3. Command Receiver verifies command with CRC
4. CRC signature is statically inserted into the Health & Status data frame
5. Health & Status frame downlinked synchronously at 1 Hz
6. Command Sender waits to see CRC signature in H&S frame to verify command was processed

**Although depicted with ground command source, this is the same protocol that is used for onboard commanding with the PGSC over RS232



Glenn Research Center


David Andrew Carek, P.E.

at Lewis Field



Protocol Algorithm

Ground Segment



Glenn Research Center

David Andrew Carek, P.E.



at Lewis Field

Uplink Command Frame

- Uplink Command Frame Format

Cmd Type	Cmd ID	Data	Timestamp	32 bit CRC	CR
----------	--------	------	-----------	------------	----

- Command ID and command type both 16 bit
- Data: optional and variable size (used mostly to uplink test parameters)
- Timestamp 32 bit (milliseconds of uptime; wraps after 49 days)
 - Timestamp guarantees unique CRC signature for every command
 - Allows discrimination of duplicate command transmission
 - Alternatively a small (1byte) wrapping sequence counter could be used

- Command Encoding


- Command generated in binary (including CRC)
- Converted to hexadecimal ASCII string (0-9,A-F)
- Carriage Return Record Terminator Added to hex string
 - Allows receiver to use simple readln call
 - Facilitates debugging (ASCII hex messages printable)
 - But ... uses double the data bandwidth
- Typically small command message size (nominally 25 bytes up to 256 bytes)



Glenn Research Center


David Andrew Carek, P.E.

at Lewis Field



Protocol Algorithm

Flight Segment




*Several outcomes of command read

Condition	Downlink Field Command ID	Downlink Field Calculated CRC	Cause
Error - Timeout Reading Input	CMD_READ_TIMEOUT	0	End of message lost (no terminator)
Error - Bad CRC	CMD_BAD_CRC	Calculated CRC (Bad CRC)	Corrupted data
Error - Message to short	CMD_BAD_CRC	Unchanged	Beginning of message lost
Success - Good CRC	Message Command ID	Calculated CRC (Good CRC)	



Glenn Research Center


David Andrew Carek, P.E.



at Lewis Field

Downlink Data Frame

- Health & Status Engineering Frame Format
 - Binary to ground (300 bytes/sec)



- 32 bit sync word – picked least likely value to occur in data
 - CM-2 mostly 12 bit A/D's with upper 4 bits unused.
Therefore 0xFFFFFFFF was an unlikely value to occur and
good choice for sync pattern (could add alternating bit if
potential for continuous stream of 0xFF)



Glenn Research Center

David Andrew Carek, P.E.



Implementation Issues


- Errors and Incompatibilities between TCP stacks
 - System crash on non-TCP packet reception
 - Problem with reconnects
- Data Packet boundaries not preserved
 - Stream preserved but packets arbitrarily fragmented
 - Parser initially designed for aggregation but not fragmentation (frames designed to fit within 1 MTU)
 - Required indexing search algorithm on CM data server (good practice anyway – TCP provides no record marker)
- Large queuing delay



Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field



Lessons Learned

- Use of TCP/IP in flight system
 - Doesn't relax testing requirements
 - sometimes makes problems more difficult to resolve due to lack of source code
 - Standards not implemented uniformly
 - RFC's hard to use as interface specifications
 - Significant cross referencing
 - Contains much more than may be used/needed by the system
 - Greatly enhances software development and testing
- Full integrated system tests required
 - Only tested on a per payload basis
 - SPACEHAB data system required patch during mission



Glenn Research Center


David Andrew Carek, P.E.

at Lewis Field



Summary of Mission Results

Analysis of Health & Status Downlink



Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field



Summary of Mission Results


- High portion of Science data downlinked
 - LSP - 50%
 - SOFBALL - 65%
 - Water Mist - 90%
- Ground Commanding Results
 - No bad CRC's detected for commanding
 - SPACEHAB up/downlink included checksum
 - Bad data discarded (not forwarded to payload)
 - Commands uplinked = 1228
 - Unique CRC's in downlink = 1067
 - Average Round Trip Time = 10 seconds



Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field



Areas for Further Investigation

- Existing Architecture
 - Quality of service provisions
 - Examine use of TCP to throttle transmission rate
 - Examine impact to real-time OS
 - Worst case S-band latency not fully understood
 - Reduce queuing latency over S-band
- Revised Architecture
 - End to end design using UDP
 - Examine SCPS-TP or gateway architecture (ref. 5)



Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field



References

1. NASA GRC, http://microgravity.grc.nasa.gov/combustion/cm/cm_index.htm
2. NASA JSC, "Space Shuttle Program Payload Bay Payload User's Guide" NSTS 21492
3. Boeing, "SPACEHAB Experiment Interface Definition Document" MDC91W5023L
4. Stone and Partridge, "When The CRC and TCP Checksum Disagree", presented at ACM SIGCOMM 2000. <http://www.acm.org/sigcomm/sigcomm2000/conf/abstract/9-1.htm>
5. CCSDS, "Space Communications Protocol Standards (SCPS): Rationale, Requirements and Application Notes" CCSDS 710.0-G-0.4,
<http://www.scps.org/Documents/717x0b1.pdf>



Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field




Extra Slides



Glenn Research Center


David Andrew Carek, P.E.

at Lewis Field



System Overview


Flight Data Systems




Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field




CM-2 Flight & Ground System Data Flow




Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field



CM-2 Ground Server Data Flow



Glenn Research Center

David Andrew Carek, P.E.



at Lewis Field

Author Biography

David Andrew Carek, P.E.

Mr. Carek is a senior research engineer in the Satellite Networks and Architectures Branch at the NASA Glenn Research Center. He is currently working on advanced communication system architecture concepts for the International Space Station. Prior to his current position, Mr. Carek managed flight software development for the Combustion Module-2 microgravity experiment. Mr. Carek has 15 years experience in computer systems integration and 7 years experience in flight software development and project management. He started his career at NASA performing structural analysis and developing computer-aided-engineering systems for advanced capabilities in structural analysis and design. Mr. Carek graduated magna cum laude in 1988 with a BSME from the University of Toledo, where he was selected as the "Outstanding Engineering Student of the Year" by the Ohio Society of Professional Engineers. Mr. Carek is a recipient of the "Silver Snoopy" award for outstanding efforts that contribute to the success of human space flight missions.



Glenn Research Center

David Andrew Carek, P.E.

at Lewis Field

